




TOP VIEW





-Joint sealant when required

Helical pipe

Plate washer under

nut on corrugated aluminum pipe

Band

END VIEW

head of bolt and

 ∞


ŰΊ


Washer under the nut for corrugated steel pipe

PLATE WASHER

UNIVERSAL COUPLING BANDS

TWO PIECE INTEGRAL FLANGE DIE FORMED BAND





8 Spaces as required

Rivets or spot welds

Bolts

Angle

Joint sealant when required

PLAN

See Detail "A" Bolts

SIDE VIEW

NOTES

END VIEW

- I. All ferrous metal coupling band connection hardware shall be galvanized or electroplated in accordance with the Standard specifications.
- 2. Dimensions and thicknesses shown are minimum.
- 3. Spot welds shall develop minimum required strength of strap.
- 4. Fillet welds of equivalent strength may be substituted for spot welds or rivets.

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

CORRUGATED METAL PIPE COUPLING DETAILS No. 3 **HELICAL AND UNIVERSAL COUPLERS**

NO SCALE

ALL DIMENSIONS ARE IN MILLIMETERS UNLESS OTHERWISE SHOWN

D97C

Std

PLAN

D97C